

PROCESS 24

HYDROREPELLENT



CONTENT

1. Documents Used
2. Purpose
3. References
4. Application
5. Safety Equipment & Tools
6. Materials
7. Consumption
8. Advantages
9. Surface Preparation
- Application
10. Packing
11. Recommendations
12. Storage
13. Observation



1. DOCUMENTS USED

CONSTRUCRIL® HIDROREPELENTE PRODUCT SHEET

2. PURPOSE

The purpose of Process 24 is to detail the application of Water repellent surface protection Construcril to provide training for the workforce and for consequently guarantee the protection of the areas.

3. REFERENCE

NBR 5829 – NBR 14725-2

4. PLACES OF APPLICATION

- Facades
- Walls
- Mortar coating
- Natural stones

- Bricks
- Ceramic Tiles
- Asbestos Cement Tiles

5. SAFETY AND TOOL EQUIPMENT

- IPE - mandatory of the work + rubber glove;
- 2 "brush;
- 4 "brush;
- Sheepskin brush or roller

6. MATERIAIS

- Construcril® HIDROREPELENTE®.

7. CONSUMPTION

- Consumption is 150 to 200 g / m2 per coat. Depending on substrate.

8. ADVANTAGES

- Easy application with brush, roller or low sprayer pressure.
- Fast drying.
- High penetration in the pores of the substrate.
- Resistant to alkalinity of small substrate residual unit.
- Point for use.
- Reduces the impregnation of dirt on the facade.
- Protects surface from water and other penetration contaminants.

9. SURFACE PREPARATION

- Surfaces must be clean of dust, particles loose, cement cream and contaminants

APPLICATION

- Apply one full coat to the point where it runs from top to bottom. using a brush, brush, roller or sprayer. low pressure.
- Apply the first coat before it gets dry, apply the second (wet on wet).

10. PACKING

- 16 kg bucket
- 3.6kg bucket

11. RECOMMENDATIONS

The use of IPE is essential.

Usual care should be taken in handling Chemicals. In case of contact with skin, wash thoroughly with water and soap for at least 15 minutes. In case of contact with eyes, rinse immediately with running water for 15 minutes. If swallowed, do not induce

PROCESS 24 HYDROREPELLENT



13. NOTE

Construcril guarantees the quality of all products assuming no responsibility for performance. work since we have no control straightforward about the application. All products must be applied as instructed in our Data Sheets Techniques and processes provided by the company in website and technical department



Equipamentos, ferramentas e materiais.